(19) World Intellectual Property Organization International Bureau



(43) International Publication Date 18 August 2005 (18.08.2005)

(10) International Publication Number WO 2005/074368 A2

(51) International Patent Classification:

Not classified

(21) International Application Number:

PCT/IL2005/000132

(22) International Filing Date: 3 February 2005 (03.02.2005)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

60/541,256

4 February 2004 (04.02.2004)

(71) Applicant (for all designated States except US): MAZOR SURGICAL TECHNOLOGIES LTD. [IL/IL]; Att: Moshe Shoham, 7 Ha'eshel Street, P.O. Box 3104, 38900 Caesarea (IL).

(72) Inventor; and

(75) Inventor/Applicant (for US only): SHOHAM, Moshe [IL/IL]; Bayit 110, Hoshaya, 17915 M.P. Hamovil (IL).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: VERIFICATION SYSTEM FOR ROBOT POSE.



(57) Abstract: An apparatus and method for assuring effective backup for sensor failure in robots, by utilizing a single extra sensor attached between the end actuator and the base. The single extra sensor provides absolute back-up for any single encoder failure that may occur in the system, and statistically significant back-up for any double encoder failure. A single additional sensor effectively provides the robotic system with one redundant information input to the robot control algorithm, which can be used in order to determine whether any of the other control sensors, or even the additional sensor itself, has failed and is delivering an erroneous reading, and hence to warn the operator of the failure. A single additional sensor also provides useful warning of the simultaneous failure of two sensors, since the likelihood that two sensors fail simultaneously in a mode that makes the failures undetectable, can be regarded as statistically insignificant.